

BOD INCUBATOR

- Temperature from 5°C to 50°C $\pm 0.5^\circ$ C. Double walled.
- Inside anodized Aluminum/Stainless steel & outside Mild steel sheet painted in epoxy powder coating.
- With perforated adjustable metal shelves. To work on 220 / 230 volts A.C.
- Two air circulating fan & transparent unbreakable Acrylic transparent door inside. Supplied with Electronic Digital Temperature/ humidifier Controller cum indicator.
- Two hours backup with 10 KVA online UPS.
- Two years warranty against any manufacturing defect.

Signature
Date: 27/11/14

Specifications for stereo binocular microscope/ Trinocular Strozoom microscope with photography attachment

- Zoom Ratio 6.7 : 1 or more
- Working distance 110 mm or more
- Transmitted and reflected LED light source
- 10x eyepiece with field number 22 or more
- Magnification Range 4.5x- 45x or more.
- live image C-MOS camera 5 mpg with image analysis software and compatible output device.
- 2 years warranty against manufacturing defect.

Note: Standard brands like Olympus, Nikon, Lica etc. will be preferred.

Def
27/11/11

Specification for Twin Litchi Pulper

- Suitable for two stage extraction of pulp from litchi fruits
- The machine should have an in-feed hopper from where the product is dumped into the pulper.
- The skin & seeds of the products should come out of other side.
- The machine should have set of sieve and set of Nylon Brush
- Capacity: 2.5-3 T/hr with 10-12 HP motor
- All the pulp contacting part of the equipment should be made up of food grade stainless steel
- The equipment should be robust, smooth finish and easy to maintain & clean
- Suitable for nonstop continuous pulping process and ISO certified.

Handwritten signature
22/11/2011

